


TPM-35

High precision optical power meter



Product Features

- 2.5mm universal interface+SC
- ±0.2 dB accuracy
- Wavelengths 850–1625nm
- Measurement range -70~+10dBm/-50~+26dBm
- Manual calibration
- Waterproof keys suitable for various outdoor environments
- Silicone jacket, anti-drop 2m
- LED lights, suitable for dark environment



Backlit display



One key start



Automatic shutdown



Resolution 0.01 dB



7 Wavelengths detection



Silicone protective jacket

Product Characteristics



Anti-fall



Compact



LED lights



Split protective jacket

TPM-35



SC



FC



ST



LC(Optional)

| | |
|---------------------|-------------------------------------|
| Wavelengths(nm) | 850/980/1300/1310/1490/1550/1625nm |
| Measurement Range | -70~+10dBm/-50~+26dBm |
| Optical Connector | 2.5mm universal interface+SC |
| Power Supply | Alkaline battery (3AA 1.5V battery) |
| Resolution (dB) | 0.01 |
| Working Temperature | -10~+60(°C) |
| Storage Temperature | -25~+70(°C) |
| Dimensions/Weight | 160x85x45mm / 220g |



Product Display



HEAD OFFICE

OrientTEK Optical Communication Ltd.

CONTACT US

Huaqiao Building, Qinheng Technology Park, North Bridge road,
Nanjing, Jiangsu, China
TEL: + 86 25 8687 0518
FAX: + 86 25 8687 0518
www.orientekot.com
sales@orientekot.com

Export Control Regulations

The products and/or technical information presented in this publication may be subject to the application of the Foreign Exchange and Foreign Trade Act and other related laws and regulations in China. In addition, the Export Administration Regulations (EAR) of the United States may be applicable. In cases where exporting or reexporting the products and/or technical information presented in this publication, customers are requested to follow the necessary procedures at their own responsibility and cost. Please contact the Ministry of Economy, Trade and Industry of China or the Department of Commerce of the United States for details about procedures.