


TPM-25m

Mini Power Meter



Product Feature

- 2.5mm universal interface
- Accuracy: $\pm 0.2\text{dB}$
- Wavelength: 850~1625nm
- Range of measurement: $-70\sim+6\text{ dBm}$ / $-50\sim+26\text{dBm}$
- Manual calibration
- Waterproof button suitable for different outdoor environment
- Mini case protection design, compact & generous
- LED lights, suitable for dark environment



Backlight display



One key start



Auto power-off



Resolution: 0.01dB



7 Wavelengths detection



Silicon protection pad

Product Characteristics



Drop resistance



Compact



LED light



Separate protective jacket

TPM-25m



SC



FC



ST



LC (Optional)

| | |
|-------------------------|--|
| Wavelength (nm) | 850/1300/1310/1490/1550/1625nm |
| Measurement range (dBm) | -70~+ 6 dBm / -50~+26dBm |
| Optical connector | 2.5mm universal interface |
| Power supply | Alkaline Battery(2 AAA 1.5V batteries) |
| Resolution (dB) | 0.01 |
| Operating temperature | -10~+60(°C) |
| Storage temperature | -25~+70(°C) |
| Dimension / Weight | 137x60x37mm / 180g |

Product Display



CONTACT US:

NANJING ORIENTEK OPTICAL COMMUNICATION LTD.

HEAD OFFICE:

Jianshan Industry Park, Liuhe District, Nanjing, Jiangsu, China

Web: www.orientekot.com

Mail: info@orientekot.com

Export Control Regulations

The products and/or technical information presented in this publication may be subject to the application of the Foreign Exchange and Foreign Trade Act and other related laws and regulations in China.

In addition, the Export Administration Regulations (EAR) of the United States may be applicable.

In cases where exporting or reexporting the products and/or technical information presented in this publication, customers are requested to follow the necessary procedures at their own responsibility and cost. Please contact the Ministry of Economy, Trade and Industry of China or the Department of Commerce of the United States for details about procedures.