

We integrate.
You communicate.

TPM-25V

Optical Power Meter & Visual Light Source





Product Feature

- 2.5mm universal interface
- wavelength: 850~1625nm
- Manual calibration
- Mini case protection design, compact & generous

- Accuracy: +0.2dB
- Range of measurement: -70~+ 6 dBm / -50~+26dBm
- Independent VFL function
- LED lights, suitable for dark environment



Backlight display



One key start



Auto power-off



Resolution: 0.01dB



7 Wavelengths detection



Silicon protection pad





Product Characteristics



Drop resistance





Separate protective jacket



LED light



TPM-25V









FC

SC LC(Optional)

ST

PARAMETER FOR OPM		UNIT	TYPICAL	NOTE
Calibration wavelength		nm	850/980/1300/1310/1490/1550/1625	
Detector	Type		InGaAs	
	Calibration accuracy	dB	±0.02	@-3dBm
	Power range	dBm	+6 ~-70dBm/-50~+26dBm	
Display nuit			dB, dBm, uW	
Optical adaptor type			2.5mm universal	
Dimension		mm	88.5(W)X57(H)X19.5(D)	
Data storage			None	
Data transmission			None	
Auto off		Min	5	
PARAMETER FOR VFL		UNIT	TYPICAL	NOTE
Central Wavelength		nm	650	Class 3b laser
Fiber compatibility			Single & Multi mode fiber	
Output power		mW	10	
Detection Distance		KM	10up	
Optical adaptor type			For SC,FC,ST	
PARAMETER FOR ELECTRIC		UNIT	TYPICAL	NOTE
Battery	Power	V	Alkaline Battery (3AA 1.5V batteries)	Typical in continuous mode
	life	hrs	50(Typ.)	
Display			LCD with back lights	
Operating temperature		°	20~75	
Storage temperature		°	-40~85	
Relative Humidity			95% RH from 0~40℃	Note









CONTACT US:

NANJING ORIENTEK OPTICAL COMMUNICATION LTD.

HEAD OFFICE:

Jianshan Industry Park, Liuhe District, Nanjing, Jiangsu, China

Web: www.orientekot.com Mail: info@orientekot.com

Export Control Regulations

The products and/or technical information presented in this publication may be subject to the application of the Foreign Exchange and Foreign Trade Act and other related laws and regulations in China. In addition, the Export Administration Regulations (EAR) of the United States may be applicable. In cases where exporting or reexporting the products and/or technical information presented in this publication, customers are requested to follow the necessary procedures at their own responsibility and cost. Please contact the Ministry of Economy, Trade and Industry of China or the Department of Commerce of the United States for details about procedures.